

Control hardware
IndraControl L25



Control hardware

IndraControl L25**Documentation**

- Project planning manual

**Advantages:**

- Scalable hardware platform
- Standardized communication interfaces
- Optional extension through function and technology modules
- Ideal for centralized and distributed control topologies
- Individually extendable with high-grade visualization components
- Modular I/O units

Technical data

		L25
Processor		
CPU		Renesas SH 7785
CPU		Renesas SH 7785
Real-time clock		integrated
Memory		
Use / application		128 MB
Remanent memory		256 kB
Flash	MByte	1
Flash size		1 GB
Display		
Type		LCD 1-line
Operation		
Type		4
		Operating keys
Interfaces		
Ethernet		1 x Ethernet TCP/IP (Standard)
Ready		1 x Ready contact (Standard)
Diagnosis		
Type		Powerfail
		Watchdog
		Temperature monitoring
I/O		
Channels, used	Max.	256
I/O extension	Max. number of Inline modules	63
	Max. number of bytes	64

Control hardware

IndraControl L25

Fieldbus		
Sercos III		1 x Sercos III (Option)
PROFINET		1 x PROFINET IO-Controller/-Device (Option)
EtherNet/IP		1 x ETHERNET/IP scanner/adapter (Option)
PROFIBUS		1 x PROFIBUS DP-Master/Slave (Option)
Electrical data		
Power supply U		24 V DC
Power supply U		24
$U_{\min} \dots U_{\max}$		19 ... 30
$U_{\min} \dots U_{\max}$		19 V DC ... 30 V DC
Residual ripple	[±%]	5
Residual ripple		+/-5 %
Logic supply U_L	[V DC]	7.5
	Max. [mA]	2
Logic supply U_L		7.5 V (transformed from external 24 V DC)
		Max. 2 A
Logic, segment supply U_{LS}	[V DC]	24
	Tolerance	-25% ... +30%
	Max. [A]	Max. 2 A
Analog supply U_{ANA}	[V DC]	24
	Max. [A]	0.5
Segment supply voltage U_S	[V DC]	24
	Tolerance	-15% ... +20 %
	Max. [A]	max. 8 A ($U_m + U_s$)
Main supply voltage U_M	[V DC]	24
	Tolerance	-15% ... +20 %
	Max. [A]	max. 8 A ($U_m + U_s$)
Power consumption	[W]	8.7
Protection		
Protection category - overall		IP20
Load		
Vibration resistance	[g]	1
Vibration resistance		1 g
Shock resistance	[g]	15
Shock resistance		15 g
Norms and Standards		
Certification		CE/UL/CSA
Environmental conditions		
Permissible temperature (operation)		+5 °C ... +55 °C
Permissible humidity (operation)		5% to 95%, EN 61131-2
Protection category		IP20
Weight		
Weight	[kg]	0.64

Control hardware

IndraControl L25**Dimensions**

Dimensions		
Height H	[mm]	120
Width B	[mm]	175.4
Length T	[mm]	84.7

System

Description	Page	Details
Motion logic system	IndraMotion MLC	Controller-based
PLC	IndraLogic XLC	

Accessories**Auxiliary components**

Description		
IndraControl L	CFL function modules	Fast I/O
IndraControl L	CFL function modules	Real-time Ethernet and PROFIBUS
IndraControl L	CFL function modules	Programmable limit switch
IndraControl L	CFL function modules	Cross communication
IndraControl L	CFL function modules	Sercos III

Ordering information

Type code	Description	Material number:
CML25.1-PN-400-NN-NNC1-NW	IndraControl L25, RT Ethernet + PROFIBUS, configurable fieldbus interface	R911172155
CML25.1-3N-400-NN-NNC1-NW	IndraControl L25, Sercos III	R911171363

Accessories

Type code	Description	Material number:
R-IB IL SCN-PWR IN-PWR	Power connector	R911171765
R-IB IL FIELD 2	Labeling field, narrow	R911289341
R-IB IL FIELD 8	Labeling field, wide	R911289342

Bosch Rexroth AG

Postfach 13 57
97803 Lohr, Germany
Bgm.-Dr.-Nebel-Str. 2
97816 Lohr, Germany
Tel. +49 9352 18-0
Fax +49 9352 18-8400
www.boschrexroth.com/electrics

Local contact information can be found at:

www.boschrexroth.com/adressen

The data specified above only serve to describe the product. As our products are constantly being further developed, no statements concerning a certain condition or suitability for a certain application can be derived from our information. The information given does not release the user from the obligation of own judgment and verification.

It must be remembered that our products are subject to a natural process of wear and aging.